UNIVERSITY OF BELGRADE

TECHNICAL FACULTY BOR

52nd International October Conference on Mining and Metallurgy

PROCEEDINGS

Edited by

Saša Stojadinović

and

Dejan Petrović

November 29th – 30th 2021

Bor, Serbia

UNIVERSITY OF BELGRADE

TECHNICAL FACULTY IN BOR

52nd International October Conference on Mining and Metallurgy

PROCEEDINGS

Edited by

Saša Stojadinović

and

Dejan Petrović

November 29th – 30th 2021

Bor, Serbia

52nd International October Conference

on Mining and Metallurgy, IOC 2021

PUBLISHER:
UNIVERSITY OF BELGRADE - TECHNICAL FACULTY IN BOR, BOR, NOVEMBER 2021

FOR THE PUBLISHER:
DEAN: Prof. dr Nada Štrbac

EDITORS:
Prof. dr Saša Stojadinović
Doc. dr Dejan Petrović

TECHNICAL EDITOR
Pavle Stojković, MSc.

PRINTED BY:
»Štamparija Atlantis d.o.o.« Niš

CIRCULATION: 100 Copies

CIP – Каталогизација у публикацији –

Народна библиотека Србије, Београд

622(082)
669(082)

INTERNATIONAL October Conference on Mining and Metallurgy (52 ; 2021 ; Bor)
Proceedings / 52nd International October Conference on Mining and Metallurgy - IOC 2021, November 29th - 30th 2021 Bor, Serbia ; [organizer] University of Belgrade, Technical Faculty in Bor ; [co-organizer Institute for Mining and Metallurgy Bor] ; edited by Saša Stojadinović and Dejan Petrović. - Bor : University of Belgrade, Technical Faculty, 2021 (Niš : Atlantis). - V, 228 str. : ilustr. ; 25 cm

Tiraž 100. - Bibliografija uz svaki rad.

ISBN 978-86-6305-119-5

а) Рударство -- Зборници б) Металургија -- Зборници

COBISS.SR-ID 52072201

ORGANIZER:

UNIVERSITY OF BELGRADE – TECHNICAL FACULTY IN BOR

Co-ORGANIZER:

INSTITUTE FOR MINING AND METALLURGY BOR

Under the Auspice of:

The Ministry of Education, Science and Technological Development of the Republic of Serbia

CONFERENCE SPONSORS

COMMITTEES

52nd International October Conference on Mining and Metallurgy, IOC 2021

SCIENTIFIC COMMITTEE

Prof. dr Nada Štrbac, (UB TF Bor, Serbia)

Prof. dr Iwao Katayama, (Osaka University, Osaka, Japan)

Prof. dr Rodoljub Stanojlović, (UB TF Bor, Serbia)

Prof. dr Radoje Pantović, (UB TF Bor, Serbia)

Prof. dr Jakob Lamut, (ULj FNT Ljubljana, Slovenia)

Prof. dr Sanda Krausz, (University of Petroşani, Romania)

Prof. dr Grozdanka Bogdanović, (UB TF Bor, Serbia)

Prof. dr Jelena Penavin Škundrić, (TF Banja Luka, B&H)

Prof. dr Seshadri Seetharaman, (Royal Institute of Technology, Stockholm, Sweden)

Prof. dr Dragoslav Gusković, (UB TF Bor, Serbia)

Prof. dr Jožef Medved, (ULj FNT Ljubljana, Slovenia)

Dr Slavomir Hredzak, (SAS Kosice, Slovakia)

Prof. dr Aleksandar Dimitrov, (FTM Skopje, FYR Macedonia)

Prof. dr Karlo Raić, (UB TMF, Serbia)

Prof. dr Snežana Šerbula, (UB TF Bor, Serbia)

Dr Ana Kostov, (IRM Bor, Serbia)

Prof. dr Kemal Delijić, (MTF Podgorica, Montenegro)

Prof. dr Stoyan Groudev, (UMG "Saint Ivan Rilski" Sofia, Bulgaria)

Dr Andrei Rotaru, (Facultatea de Mecanica, Romania)

Prof. dr Krzystof Fitzner, (AGH University, Krakow, Poland)

Prof. dr Sulejman Muhamedagić, (FMM Zenica, B&H)

Prof. dr Anđelka Mihajlov, (Educons University, Serbia)

Prof. dr Luis Filipe Malheiros, (FEUP, Porto, Portugal)

Prof. dr Svetlana Ivanov, (UB TF Bor, Serbia)

Prof. dr Batrić Pešić, (Materials Science Faculty, Idaho, USA)

Prof. dr Ljubica Ivanić, (UB TF Bor, Serbia)

Dr Srećko Stopić, (RWTH Aachen, IME Aachen, Germany)

Prof. dr Boštjan Markoli, (ULj FNT Ljubljana, Slovenia)

Dr Magnus Ericsson, (Lulea Technical University, Stockholm, Sweden)

Prof. dr Tamara Holjevac Grgurić, (MF Sisak, Croatia)

Prof. dr Boyan Boyanov, (University Paisiy Hilendarski, Plovdiv, Bulgaria)

Prof. dr Milan Antonijević, (UB TF Bor, Serbia)

Prof. dr Tatjana Volkov-Husović, (UB TMF, Serbia)

Prof. dr Branka Jordović, (TF Čačak, Serbia)

Prof. dr Milan Trumić, (UB TF Bor, Serbia)

Prof. dr Tomaš Havlik, (TUKE, Slovakia)

Prof. dr Carl Heinz Spitzer, (TU Clausthal, Germany)

Dr Mile Bugarin, (IRM Bor, Serbia)

Prof. dr Velizar Stanković, (UB TF Bor, Serbia)

Prof. dr Costas Matis, (AU Thessaloniki, Greece)

Dr Milenko Ljubojev, (IRM Bor, Serbia)

Prof. dr Velimir Radmilović, (University of California at Berkeley, USA)

Prof. dr Dejan Tanikić, (UB TF Bor, Serbia)

Dr Mirjam Jan-Blažić, (Slovenian Foundryen Society, Slovenia)

Prof. dr Vitomir Milić, (UB TF Bor, Serbia)

Prof. dr Desimir Marković, (UB TF Bor, Serbia)

Prof. dr Mirjana Rajčić Vujasinović, (UB TF Bor, Serbia)

Dr Vladan Ćosović, (UB IHTM, Serbia)

Prof. dr Dimitris Panias, (NTUA, Athens, Greece)

Prof. dr Mirko Gojić, (MF Sisak, Croatia)

Prof. dr Vladimir Krstić, (Queen's University, Canada)

Prof. dr Dimitriu Sorin, (Polytechnic University of Bucharest, Romania)

Dr Miroslav Sokić, (UB ITNMS, Serbia)

Prof. dr Vladislav Kecojević, (West Virginia University, USA)

Prof. dr Dragan Manasijević, (UB TF Bor, Serbia)

Prof. dr Mirsada Oruč, (FMM Zenica, B&H)

Prof. dr Vlastimir Trujić, (IRM Bor, Serbia)

ORGANIZING COMMITTEE

Prof. dr Saša Stojadinović, vanredni profesor, UB, TF Bor

Prof. dr Ljubiša Balanović , vanredni profesor, UB, TF Bor

Doc. dr Dejan Petrović, docent, UB, TF Bor

dr Ana Kostov, naučni savetnik, Institut za rudarstvo i metalurgiju Bor

Doc. dr Aleksandra Mitovski, docent, UB, TF Bor

Doc. dr Ana Simonović, docent, UB, TF Bor

Prof. dr Jovica Sokolović, vanredni profesor, UB, TF Bor

Prof. dr Đorđe Nikolić, redovni profesor, UB, TF Bor

Doc. dr Uroš Stamenković, docent, UB, TF Bor

Prof. dr Milan Radovanović, vanredni profesor, UB, TF Bor

Doc. dr Danijela Voza, docent, UB, TF Bor

Jelena Ivaz, asistent, UB, TF Bor

Pavle Stojković , asistent, UB, TF Bor

Mladen Radovanović , asistent, UB, TF Bor

Predrag Stolić , asistent, UB, TF Bor

Kristina Božinović , asistent, UB, TF Bor

Sandra Vasković, Nastavnik engleskog jezika, UB, TF Bor

Oliver Marković, šef IKTC, UB, TF Bor

Miomir Voza, laborant, UB, TF Bor

TABLE OF CONTENTS

Aleksandra Milosavljević

THE COMPLEXITY OF SEM-EDS – WHAT AFFECTS THE QUALITY OF OBTAINED RESULTS? 1

Zoran Karastojković, R Perić, M Srećković

LASER QUENCHING OF CUTTING TOOL STEELS - A REVIEW 5

Slavica Miletić, D Bogdanović, E Požega

IMPACT OF EXTRAORDINARY SECURITY MEASURES TO EMPLOYEES DURING THE PANDEMIC COVID-9 15

Daniela Grigorova, R Paunova

KINETIC STUDY OF SOLID-PHASE REDUCTION OF POLYGRADIENT IRON-CONTAINING MATERIAL 19

Emina Požega, D Simonović, S Marjanović, M Jovanović, L Gomidželović, M Mitrović, Z Stanojević Šimšić

PART I: WHAT MAKES A GOOD THERMOELECTRIC 23

Emina Požega, D Simonović, S Marjanović, M Jovanović, L Gomidželović, M Mitrović, S Miletić

PART II: WHAT MAKES A GOOD THERMOELECTRIC 27

Dragan Manasijević, Lj Balanović, I Marković, M Gorgievski, U Stamenković, K Božinović, D Minić, M Premović

STUDY OF MICROSTRUCTURE AND THERMAL CONDUCTIVITY OF THE Ag–Bi–Sn ALLOYS 31

Vladimir S. Topalović, S Matijašević, S Grujić, J Stojanović, J Nikolić, V Savić, S Zildžović

THE INFLUENCE OF THE PARTICLE SIZE ON CRYSTALLIZATION OF GLASS POWDERS FROM THE SYSTEM Li_2O-Al_2O_3-GeO_2-P_2O_5 35

Vesna Marjanović, R Marković, V Krstić

TECHNOLOGIES FOR PHYSICAL TREATMENT OF WATER CONTAINING SELENIUM: A REVIEW 39

Vesna Marjanović, R Marković, V Krstić

TECHNOLOGIES FOR BIOLOGICAL TREATMENT OF WATER CONTAINING SELENIUM: A REVIEW 43

Milenko Jovanović, M Mikić, M Maksimović, D Kržanović, R Rajković, E Požega

USAGE SPECIFICS OF GEOGRIDS 47

Srećko Manasijević, Z Zovko Brodarac, N Dolić, M Djurdjević, R Radiša

INTERMETALLIC BONDING BETWEEN A RING CARRIER AND AN ALUMINUM PISTON ALLOY **51**

Snežana Šarboh

PATENTED INVENTIONS OF LJUBOMIR KLERIĆ **55**

Miomir Mikic, M Jovanović, R Rajković, D Kržanović, E Požega

DEGRADED AREA OF VELIKI KRIVELJ QUARRY RECULTIVATION **59**

Dragana Adamović, D Ishiyama, H Kawaraya, O Yasumasa

EFFECTS OF TAILINGS ON GROUNDWATER ALONG BOR AND BELA RIVERS IN THE BOR MINING AREA, EASTERN SERBIA **63**

Ana Kostov, Z Stanojević Šimšić, A Milosavljević,

CHARACTERIZATION OF ALLOYS CuAlAu0.5 **67**

Marija Milenković, V Jovanović, J Paunković, V Krstić

MULTICRITERIA ANALYSIS OF THE LEVEL OF SUSTAINABLE DEVELOPMENT OF THE TOPLICA DISTRICT USING THE ELECTRE METHOD **71**

Daniel Kržanović, R Rajković, D Stevanović, M Mikić, M Jovanović, S Petrović

LONG-TERM PLANNING OF MINING THE LEAD AND ZINC ORE DEPOSIT IN THE BRSKOVO ORE FIELD, THE REPUBLIC OF MONTENEGRO **75**

Radmilo Rajković, D Kržanović, M Mikić, M Jovanović

CALCULATION OF SAFETY DISTANCE FOR THE OPERATION OF MINING EQUIPMENT IN THE WORKING ENVIRONMENT WITH WEAKENED CHARACTERISTICS AT THE OPEN PIT "NORTH MINING DISTRICT" OF THE COPPER MINE MAJDANPEK **79**

Zdenka Stanojević Šimšić, A Kostov, A Milosavljević, E Požega

HARDENSS, MICROHARDNESS AND ELECTROCONDUCTIVITY OF ALLOYS WITH VARIABLE Cu CONTENT IN Cu-Al-Ag SYSTEM **83**

Miodrag Banješević

STRATIGRAPHY AND AGE OF ROCK UNITS AND MINERALIZATION IN THE TIMOK MAGMATIC COMPLEX ANDTHE BOR METALLOGENIC ZONE – A REVIEW **87**

Milan Radivojević, Z Stević, M Tanasković

DUALPHASED FOURWAYINTERSECTION REGULATED BY TRAFFIC LIGHTS WITH FIXED AND ADAPTIVE MOD OF OPERATION **93**

Filip Gramić, N Rančić, S Filipović, J Đorđević

USE OF COPPER TAILING AND COPPER SLAG IN D PRINTED CONCRETE PROCESSES **97**

Filip Gramić, N Rančić, S Filipović, J Đorđević,

POSSIBILITY OF USING MINING WASTE IN THE PRODUCTION OF BRICK PRODUCTS **101**

Stepan O. Vydysh

GOLD-SILVER ALLOYS ANODIC DISSOLUTION RESEARCH IN HYDROCHLORIC ACID ELECTROLYTES **105**

Milan Gorgievski, M Marković, D Božić, Vr Stanković, N Štrbac, V Grekulović, M Zdravković

ADSORPTION ISOTHERMS FOR COPPER IONS ADSORPTION ONTO WALNUT SHELLS **109**

Miljan Marković, M Gorgievski, N Štrbac, V Grekulović, A Mitovski, K Božinović, M Zdravković

pH AND CONDUCTIVITYCHANGE DURING THE RINSING AND ADSORPTION OF COPPER IONS ONTO WALNUT SHELLS **113**

Vesna Grekulović, A Mitovski, M RajčićVujasinović, N Štrbac, M Zdravković, M Gorgievski, M Marković

ELECTROCHEMICAL BEHAVIOR OF COPPER IN CHLORIDE MEDIUMIN THE PRESENCE OF WALNUT SHELL MACERATE **117**

Marija Šljivić-Ivanović, S Dimović, I Jelić,

EXPERIMENTAL DESIGN APPROACH IN RADIONUCLIDE SORPTION **121**

Ivana Jelić, A Savić, M Šljivić-Ivanović, S Dimović

INFLUENCE OF SILICA FUME ON SCC CONCRETE PROPERTIES **125**

Milan Radovanović, A Simonović, M Petrović Mihajlović, Ž Tasić, V Nedelkovski, M Antonijević

L-LYSINE AS CORROSION INHIBITOR OF STAINLESS STEEL IN RINGER'S SOLUTION **129**

Dragana Marilović, M Trumić, M Trumić,Lj Andrić

THE INFLUENCE OF CALCIUM IONS ON DEINKING FLOTATION RECOVERY UNDER DIFERENT CONDITIONS **133**

Dragana Medić, S Milić, S Alagić, M Nujkić, S Đorđievski, A Papludis

OPTIMIZATION OF CATHODIC MATERIAL LEACHING PROCESS IN ACID-SULPHATE SOLUTION **137**

Milijana Mitrović, D Gusković, S Marjanović, BTrumić, E Požega, U Stamenković, J Petrović

OBTAINING MULTILAYER COPPER STRIPS BY ARB (ACCUMULATIVE ROLL BONDING) ROLLING PROCESS **141**

Nataša Đorđević, S Mihajlović, N Obradović, A Peleš, S Filipović

THE INFLUENCE OF HIGH COMPACTION PRESSURE ON CORDIERITE-BASED CERAMICS **145**

Nataša Đorđević, S Mihajlović, M Sokić, B Marković

SEM AND X-RAY ANALYSES OF SINTERED MgO / Bi_2O_3 BINARY SYSTEM **149**

Ivana Ilić, J Sokolović, M Trumić, Z Stirbanović

COMPARATIVE RESULTS OF COPPER FLOTATION FROM SLAG BEFORE AND AFTER THE PROCESS OF MAGNETIC CONCENTRATION **153**

Daniela Grigorova

FERROSILICON OBTAINING USING IRON-SILICATE –FAYALITE **157**

Slavica Mihajlović, M Jovanović, N Đorđević, A Patarić, M Vlahović, V Kašić

THE CLAY PRELIMINARY TESTING FROM MUNICIPALITY AREA OF REKOVAC **161**

Milan Milosavljević, M Premović, D Minić, Dn Mansijević, Ar Đorđević, M Kolarević

EXPERIMENTAL AND THERMODYNAMIC STUDY OF ISOTHERMAL SECTIONS AT 600 °C AND 400 °C OF TERNARY Bi-Cu-Ge SYSTEM **165**

Aleksandar Đorđević, D Minić, M Premović, D Mansijević, M Milosavljević, V Ristić

STUDY OF TEMPERATURE PHASE TRANSFORMATION OF THETERNARY Bi-Cu-Ge SYSTEM **169**

Aleksandar Savić, I Jelić, M Šljivić-Ivanović, S Dimović, N Pudar, A Pfandler

RECYCLED COARSE AGGREGATE AND FLY ASH EFFECT ON COMPRESSIVE STRENGTH OF SELF-COMPACTING CONCRETE **173**

Vladan Kašić, D Životić, V Simić, A Radosavljević-Mihajlović, J Stojanović, S Mihajlović, M Vukadinović

FORECAST RESOURCES OF ZEOLITHIC TUFFS OF SERBIA **177**

Vladan Kašić, A Radosavljević-Mihajlović, S Radosavljević, J Stojanović, S Mihajlović, M Vukadinović

GEOLOGICAL AND MINERAL CHARACTERISTICS OF ZEOLITHIC TUFF TOPONICA DEPOSITS NEAR KOSOVSKA KAMENICA **181**

Konstantin Petkov, V Stefanova, P Iliev

METHOD FOR UTILIZATION OF THE SULFURIC ACID OBTAINED DURING AUTOCLAVE DISSOLUTION OF PYRITE CONCENTRATE **185**

Stefan Đorđievski, D Ishiyama, Y Ogawa, Z Stevanović, O Osenyeng, D Adamović, V Trifunović

MONITORING OF pH VALUE AND CONCENTRATION OF COPPERIN RIVERSDOWNSTREAM FROM BOR MINE IN PERIOD 2015-2021 **189**

VišaTasić, M Cocić, B Radović, T Apostolovski-Trujić

CHEMICAL COMPOSITION OFPARTICULATE MATTER IN THE INDOOR AIRAT THE TECHNICAL FACULTY IN BOR (SERBIA) **193**

Snežana Ignjatović, I Vasiljević, M Negovanović

DEFINING STRUCTURAL CORRELATION USING OF TOTALHORIZONTAL GRADIENT **197**

Velizar Stanković, M Janošević

INCREASING THE CAPACITY OF THE COPPER SMELTING COMPANY IN THE COMPANY "SERBIA ZIJIN COPPER" - CHALLENGES AND CONSEQUENCES TO THE ENVIRONMENT **201**

Vladimir Jovanović, D Todorović, B Ivošević, D Radulović, S Milićević, D Nišić

CHARACTERIZATION OF PELLET SAMPLES OBTAINED BY PELETIZATION OF LIMESTONE AND SEAWEED **205**

Vanja Trifunović, L Avramović, R Jonović, S Milić, S Đorđievski, M Jonović

HYDROMETALLURGICAL TREATMENT OF ELECTIRIC ARC FURNACE DUST IN AIM OF ZINC SEPARATION **209**

Jovana Bošnjaković, N Knežević, N Čutović, M Bugarčić, A Jovanović, Z Veličković, S Manasijević

EVALUATION OF ADSORPTION PERFORMANCE OF PHOSPHATES REMOVAL USING CELL-MG HYBRID ADSORBENT **213**

Dragan Radulović, Lj Andrić, D Božović, V Jovanović, B Ivošević, D Todorović,

POSSIBILITY OF USING LIMESTONE FROM "PJEŠIVAČKI DO"-DANILOVGRAD DEPOSIT AS FILLER IN VARIOUS INDUSTRY BRANCHES **217**

Predrag Stolić, J Ivaz, D Petrović, Zoran Stević

ADVANTAGES OF MINING ENGINEERING CURRICULUM REALIZATION USING SOLUTIONS BASED ON FREE SOFTWARE **221**

Slađana Krstić, E Požega, S Petrović, S Magdalinović, D Urošević, S Miletić, Z Stojanović Šimšić

QUALITY INVESTIGATION OF SAND FOR THE PRODUCTION OF AGGREGATES ON VINOGRADI LOCALITY (DELIBLATSKA PEŠČARA) **225**

Saša Marjanović, D Gusković, M Mitrović, E Požega ,B Trumić, U Stamenković

INFLUENCE OF COLD ROLLING AND ANNEALING ON HARDNESS OF BIMETALLIC STRIP Cu– Al **229**

The 52nd International October Conference on Mining and Metallurgy
November 29th – 30th , 2021
www.ioc.tfbor.bg.ac.rs

DUALPHASED FOURWAYINTERSECTION REGULATED BY TRAFFIC LIGHTS WITH FIXED AND ADAPTIVE MOD OF OPERATION

Milan Radivojević[1*], Zoran Stević[2], Marko Tanasković[3]

[1]Mining and Metallurgy Institute Bor, Zelenibulevar 35, 19210 Bor, Serbia

[2]Technical Faculty Bor, University of Belgrade, V.J. 12, 19210 Bor, Serbia

[3]UniversitySingidunum Belgrade, ul. Danijelova 32, 11000 Belgrade, Serbia

Abstract

Road traffic in many populated areas is mainly regulated using a traffic light, which in many cases is not sufficiently effectively configured. This can lead to unnecessary long waiting times and increase total time losses when passing through the intersection. This paper presents the results of the application program of the adaptive semaphore system of the four-way two phase intersection, made using the LabVIEW software package, as well as the data and results of the analysis of the functioning of the intersection with adaptive and fixed traffic mode.

Keywords: *adaptive traffic mode, fixed traffic mode, traffic regulation, traffic lights, virtual instrument.*

1. INTRODUCTION

From the functional point of view, surface intersection is the most complex element of the traffic network.Namely, the paths of traffic flows of different directions are crossed, the flows may change directions, the vehicle and pedestrian flows are crossed, different maneuvers take place. This indicates that surface intersections are areas with increased concentration of conflicts and increased risk of traffic accidents. That is precisely why it is necessary to have in mind that, while designing and constructing intersections,their main role is to ensure safe traffic and quickly and economically distribute traffic flows, in order to ensure that the conflicts among the participants in traffic are less frequent and that the congestion delay is as little as possible. These conditions have to be met by using minimal financial investments.

The main role of the traffic lights, i.e. light signals for traffic regulation at surface intersections, is the separation of conflicts between vehicles and pedestrians at characteristic points. Light signals regulate traffic flows in such a way as to allow vehicles of one group of flows (non-conflict or conflict-compatible) to pass in a given time period (phase), whereby the vehicles of the second group of flows will be collected at the same time. Then, the second group of vehicles is accommodated, during the same, or different time interval, then the third, possibly the fourth and so on, after which the cycle is repeated periodically. Vehicle accommodation is carried out on the basis of a signalling plan, which, in a unified way, accommodates all the flows grouped within the phases. The main problem that needs to be solved, when it comes to signalized intersection, is calculating and optimization of the signal plan, which implies determining the cycle duration, the number of phases, as well as calculating the distribution of green time intervals to each phase. The maximum recommended duration of the cycle is 120sec. Light signals can operate in a fixed mode when signal plans are determined based on previously collected traffic data, and also as adaptive systems, when light signals operate depending on changes in traffic parameters such as flow, speed, density, and more.

2. THE CYCLE, CAPACITYAND DEGREE OF SATURATIONOF THESURFACE INTERSECTION

The Webster method is used in order to determine the duration of the cycle (C) and the green times of the corresponding phases (gi) of the traffic lights:

$$C = \frac{1.5 \cdot L + 5}{1 - Y},\ g_i = \frac{Y_i}{Y} \cdot (C - L),\ L = n \cdot d + \sum_{i=1}^{n} \Delta t_i \ \text{i} Y = \sum_{i=1}^{n} Y_i \qquad (1)$$

where: L - represents the total lost or unused time at the intersection during the cycle, Yi = maxj {yj (i)} = maxj (Qi / Si) and yi = Qi / Si - the coefficient of utilization capacity of the i-traffic lane, number of phase of the signal plan, d - average time losses-congestion delays, per vehicle during the "green phase" and Δti – clearance interval between the phase "i" and the next phase. The Qi, Si and Y represent the traffic flow intensity of the i-th access lane,the saturated traffic flow of the i-th lane and the coefficient of utilization of the intersection capacity. Saturated traffic flows are determined on the basis of special tables and, as a rule, for this intersection, are constant.On the other hand, the intensity of traffic flows Qi can change over time (daily, weekly, monthly, etc) and are most often determined by counting or by using special detectors installed at the intersections. Intersections with constant cycle values are constant, calculated on the basis of pre-collected data on traffic flow intensity values, constitute a group of intersections with a fixed mode of traffic light system operation.

The intersections where the optimum cycle value is calculated and the distribution of green time to each phase is carried out in such a way that the values are adapted to the changes in traffic flows, belong to the group of intersections with the adaptive system of traffic lights mode of operation.

Adaptive traffic management systems are very complex systems. The functioning of such systems, as a rule, is based on the use of computer systems and corresponding software solutions. The basic components of the adaptive system are the data parameters, the traffic parameters, the corresponding computer system, the light source controller and the traffic lights (Figure 1a.).



Figure 1. System elements and cycle calculation



Figure 2. Functional structure of the adaptive system

Figure 2 shows the functional structure of the adaptive traffic management system at intersections regulated by traffic lights.

The aim of this paper is to offer one of the possible solutions for an adaptive traffic management system, based on the use of LabView software package. The basis of the solution lies in the fact that is necessary is to the measure of the intensity of traffic flows in the intersection lanes, during

the current cycle (with the help of appropriate detectors), and use the values to calculate the duration of the next cycle (Figure 1b.):

$$C_{k+1} = (1.5L_k + 5)/(1 - Y_k) \quad (2)$$

where k represents the current cycle and, in accordance with the relation (1) and the length of the green light for each phase, the capacity (ci), the saturation level (Xi) for each traffic lane:

$$g_{i,k+1} = (Y_{i,k}/Y_k)(C_{k+1} - L_k), \; c_{i,k+1} = S_i(g_{i,k+1}/C_{k+1}) \text{i} X_{i,k+1} = Q_{i,k}/c_{i,k+1} \quad (3)$$

When the saturation values for all traffic lanes are equal or less than one, then, the traffic takes place under conditions of unsaturated traffic flows, which means that vehicles stop only once in front of the stop line, and that all vehicles that "requested" pass through the crossroads are accommodated during the cycle. If the saturation level is larger than one, on one or more lanes, then the traffic takes place under conditions of oversaturated flows, which means that not all vehicles are accommodated during the cycle and that a certain number of vehicles stop several times before they pass through the intersection.This further leads to a significant increase in congestion delays, as well as an increase in the concentration of exhaust gases, increased anxiety and other undesirable occurrences.

3. RESULTS OF TESTING THE ADAPTIVE SYSTEM PROGRAM SOLUTION

The program solution for the adaptive traffic management system is calculated for a four-way, two phased isolated intersection regulated by traffic lights. The solution is based on the software platform called LabVIEW software package - a standard in the field of virtual instrumentation.

The graphic user interface package has two panels: a control panel for process control and tracking and a panel for making an application solution, or a block diagram. The testing of the software solution and comparing the obtained results was performed on two identical two-phase intersections, one of which works with the adaptive, and the other with a fixed traffic light mode of operation (with a cycle duration of 52 seconds). The testing was carried out by computer simulation, where the simulation program was also done in LabVIEW. This program is, in its essence, identical to that used by an adaptive mode of operation of traffic lights in real-life conditions. The only difference is that a special simulator (instead of the appropriate detectors) is used as the basis for the traffic flow in the simulation program, and that the elements of the signal timing plan are sent directly to the traffic lights. Figures 3 and 4 show the results of the test, ie the average value of traffic flows at the end of the current cycle (used to calculate the duration of the next one) and saturation levels within the respective cycles.



Figure 3. Average values of traffic flows during testing times at intersections crossings with adaptive and fixed mode

The test results show (Figure 4) the advantages of adaptive mode of operation in relation to the intersections with the fixed mode of traffic lights operation. In the first one the traffic takes place in unsaturated traffic flows and with significantly smaller changes in the degree of saturation. However, the intersection with a fixed mode of operation, after the fourth cycle, undergoes the

state of oversaturated flows, and under such circumstances, with minor changes, the traffic takes place until the end of the test period.



Figure 4. Levels of saturation of intersection with adaptive and fixed mode of traffic light

4. CONCLUSION

The testing process was carried out for different cycle lengths of the system with a fixed mode of operation and different values of average traffic flows, and results are similar to those shown in the following tables. The software solution shows the benefits of the adaptive system when vehicles are in the dilemma zone, and when emergency vehicles are passing through the intersection.

The development of computers, the rapid development of new technologies and different types of sensors for detecting conditions and traffic parameters data, have enabled the creation of adaptive systems designed to control the light signals operation, not only on isolated and intersections regulated by traffic lights, but also on at-grade intersection. Nowadays, there is a large number of adaptive systems around the world installed in different locations, use different equipment, work under different conditions and achieve different results. What is common to most systems is the lack of information on essential modes of operation, used algorithms and other elements of management control.

ACKNOWLEDGEMENTS

This work was financially supported by the Ministry of Education, Science and Technological Development of the Republic of Serbia, Grant No. 451-03-9/2021-14/ 200052.

REFERENCES

[1] Krsto P. Lipovac, BEZBEDNOST SAOBRAĆAJA, udžbenik, Beograd, 2008, 105-188

[2] Docent drŽeljkoRanković, dipl.ing., Regulisanjesaobraćaja (Materijalsapredavanja), TEHNIKUM TAURUNUM, Visokainženjerskaškolastrukovnihstudija Beograd – Zemun, smerDrumskiigradskisaobraćaj, Beograd, 2011, p. 85

[3] *CALCULATION OF TRAFFIC SIGNAL TIMINGS - WEBSTER'S METHOD,* http://www.rhd.gov.bd/Documents/ExternalPublications/Trl/Calculation%20of%20traffic%20signal%20timings-Webster's%20method%20Note13.pdf, p. 7.

[4] Mingmin Wu, Wanjing Ma, Li Li, Characterize Dilemma Zone and Minimize its Effect *at Coordinated Signalized Intersections,*https://core.ac.uk/download/pdf/82213153.pdf, p.13

[5] *Priručnik za projektovanjeputeva u RepubliciSrbiji*, Funkcionalnielementiipovršineputeva, Raskrsniceipriključci, JavnopreduzećePuteviSrbije, Beograd, 2012, p. 25.

ISBN 978-86-6305-119-5